

## INTRODUCTION

### CONTENERGY ISO

The dimensions of CONTENERGY ISO containers comply with CSC certification. They have been specially designed to withstand significant loads and pressures during transport without incurring damage, and for ship transportation without any special constraints. They are available in two sizes: 20 and 40 feet "High Cube".

### CONTENERGY CIR

CIR type containers are more suited to mobile and rental applications. This highly compact model has a very low sound level and features an optional high volume tank, giving it up to 10 hours of autonomy. This model is available as a 20 feet "High Cube"



For environmental protection purposes our containers may be fitted with an optional retention container to hold all engine fluids.

Our containers comply with all current standards and regulations governing these products, including:

- ISO 668
- NF90-005
- NF ISO 1496-1 (ISO 8323)



ISO20 (Silent)  
1275kVA - 1540kVA



CIR20 SSI (Super Silent)  
1275kVA - 1540kVA



ISO40 (Silent)  
1700kVA - 2100kVA

Generating set type	Engine	SILENT	SUPER SILENT	SILENT	SUPER SILENT
		85-87 dB(A)@1 m	82-84 dB(A)@1 m	79-82 dB(A)@7 m	77-79 dB(A)@7 m
T1400 - T1540	S12R	ISO 20 Si	CIR 20 SSi	X	X
T1200U - T1350U	S12R	X	X	ISO 20 Si	CIR 20 SSi
T1900 - T2100	S16R	ISO 40 Si	X	X	X
T1600U - T1800U	S16R	X	X	ISO 40 Si	X