



**SDMO
PRODUCT
PLUS**

The gensets from the PACIFIC range are the winning combination between robustness and easy use

PACIFIC range 50Hz



T1400



T1540

TECHNICAL SPECIFICATIONS

50Hz range

RANGE	Specifications 50 Hz 400-230 V				Engine specifications						Alternator	Compact version ⁽⁴⁾	
	GENE-RATING SETS ⁽¹⁾	kVA Cos 0,8		Cons 3/4 L/h	Engine type	cyl	Bore (mm)	Stroke (mm)	Cyl (L)	Type	Dimensions LxIxh (m)	Weight ⁽⁵⁾ (kg)	
		PRP ⁽²⁾	ESP ⁽³⁾										
PACIFIC II	T1400	1275	1403	208	S12R-PTA	12	170	180	49,03	501M7	4,33x2,00x2,37	9781	
	T1540	1400	1540	218	S12R-PTA2	12	170	180	49,03	501L8	4,42x2,00x2,37	10147	
	T1900	1727	1900	266	S16R-PTA	16	170	180	65,37	512S55	5,50x2,29x2,48	12891	
	T2100	1909	2100	304	S16R-PTA2	16	170	180	65,37	512M60	5,60x2,29x2,48	13314	
	T2200	2000	2200	307,3	S16R-PTAA2	16	170	180	65,37	512M60	5,50x2,29x2,58	14371	

(1) Also available in the following voltages: 415/240 V - 380/220 V

(2) PRP: Prime power available continuously at variable load for an unlimited number of hours per year in accordance with ISO 8528-1, an overload of 10% is available for one hour in 12 hours in accordance with ISO 3046-1

(3) ESP: Standby power available for emergency use at variable load in accordance with ISO 8528-1, no overload available with this service.

(4) The dimensions and weights apply to a generating set specified in the price list, without options

(5) Dry weight - without fuel