

Standard containers

basic and options

50Hz 60Hz

BASIC AND OPTIONS

EQUIPMENT

	Basic and options	SILENT			SUPER SILENT	
		ISO 20 Si	ISO 40 Si	ISO 40 Si	CIR 20 SSi	EUR 40 SSi
Basic	Base member	•	•	•	•	•
	Starter motor, 24 V charging alternator	•	•	•	•	•
	Batteries filled with electrolyte	SO 001	SO 001	SO 001	SO 001	SO 001
	Standard air filter	•	•	•	•	•
Container specifications	Oil drainage pump	•	•	•	•	•
	Type of soundproofing	Si	Si	Si	SSi	SSi
	High performance integrated 30 dB(A) silencer	•	•	•	•	•
	Floor	Bulb plate	Bulb plate	Bulb plate	Bulb plate	Bulb plate
	Number of doors	2	2	2	3	3
	Galvanised air outlet rain grille	CT 005	CT 005	CT 005	•	•
	Safety lighting and shut-off valve	CT 007	CT 007	CT 007	CT 007	CT 007
	Exhaust outlet on bracket	CT 011	CT 011	CT 011	CT 011	CT 011
	RAL 9010 white painted finish for container	•	•	•	•	•
	Special colour from list	CT 016	CT 016	CT 016	CT 016	CT 016
Fuel	Power cable outlet on lower section	CT 015	CT 015	CT 015	CT 015	X
	Retention container under container assembly	CT 014	CT 014	CT 014	CT 014	CT 014
	500 l chassis tank	•	X	X	•	X
	Tank on container (500 l)	X	•	•	X	•
	Tank on container (2000 l)	X	X	X	CT 017	CT 017
	External terminal block	CT 018	X	X	CT 018	CT 018
	1m ³ /h pump auto kit 1	CT 008	CT 008	CT 008	CT 008	CT 008
	1m ³ /h pump auto kit 2	X	CT 009	CT 009	X	CT 009
	4m ³ /h pump auto kit 2	X	CT 010	CT 010	X	CT 010
	CE compliance of the control unit	•	•	•	•	•
Control units	TELYS central console	CM 40	CM 40	CM 40	CM 40	CM 40
	KERYS control unit	CA 600	CA 600	CA 600	CA 600	CA 600
Dimensions	Length (mm)	6058	12192	12192	6058	12192
	Width (mm)	2438	2438	2438	2438	2438
	Height (mm)	2896	2896	2896	2896	2591

9

• As standard X Not available EN 01 Option code CT 011 Free option

ENCLOSURE

If you wish to soundproof a generating set fitted with an MTU-DDC 12V2000 or 16V2000 engine, while keeping the size to a minimum, you should choose the M427 enclosure.

This will enable you to mount the assembly inside a 40 feet "High Cube" container to facilitate transportation.

ENCLOSURE	Specifications 50 Hz				60Hz specifications				General specifications	
	Generating set type	dB(A)@1m	dB(A)@7m	Weight	Generating set type	dB(A)@1m	dB(A)@7m	Weight	Dimension lxxh	Fuel
427	X715/X715C	90	80	7836	X700UC2	94	85	7836	6.4x2.17x2.72	930
427	X880/X880C	91	81	8036	X800UC2	94	85	8236	6.4x2.17x2.72	930
427	X1000/X1000C	90	80	8604	X900UC2	95	86	8604	6.4x2.17x2.72	930
427	X1100/X1100C	91	81	8709	X1000UC2	95	86	8909	6.4x2.17x2.72	930



M427